



F24-60[®]

Joystick Controller

Double Joystick with

5 steps



Reliable - High Performance - Economic

F24-60 serie is best for Tower Cranes, Overhead Cranes and Concrete Pumps.
F24-60 is equipped with most advanced safety features for making the entire operation safe.

FEATURES

- Fully programmable relay configuration with maximum 16 relays output per command. (NO extra extension unit required)
- Durable nylon-fiber housing for extra shock resistance.
- Operating range up to 100 meters.
- Pre-wiring standard cable making installation quick and easy.
- New waist belt provide maximum comfort for operator (Optional)
- 3 stages LED battery power indicator
- Acceleration delay time control (Providing smooth moving for multiple speeds cranes)
- Safety features:
 - 4.3 billion unique ID code
 - Hamming code
 - Enhanced Watch-Dog circuit

Double Joystick with

5 steps ←



Transmitter / Receiver / General Specification

| Transmitter | General Specification | Receiver |
|--|---|----------|
| Double Joystick/ 6 Single step buttons (Including start button) | Operating Temp. -35°C ~ +80°C | |
| 1 Emergency button (EMS) | Operating Range 100 M | |
| 1 Rotary key switch | TX power supply 4 AA size Alkaline / Rechargeable Battery | |
| 4 selector switches | RX power supply AC 48/110/220/380 V | |
| | Protection class IP 65 Industrial standard | |
| | ID Code 4.3 billion (32 bit) | |
| | Hamming distance ≥ 4 | |
| Max. 40 relay output (Programmable) | TX Dimension & Weight 220 x 110 x 90 mm Apprx. 860g (w/o batteries) | |
| NC/NO relay (optional) | RX Dimension & Weight 290x230x70mm Apprx. 2200g (w/o cable) | |
| External passive antenna (optional) | | |

F24-60 Accessories

CD Software
& Program Cable

Copier

Battery Charger

Passive Antenna

Waist belt



Telecrane other series

F21-PLL Series



- * 8/12 single/double step pushbuttons.
- * PLL Synthesizer radio frequency control

F21-Crystal Series



- * 2/4/6 single/double step pushbuttons
- * AC power supply is suitable for small crane/chain hoist
- * Also available with DC power supply (12~24VDC) suitable for mobile application

F24 Series



- * 8/10 single/double step pushbuttons
- * Economic model best for overhead crane.

Itahydraulic
Power Technology



TELECRANE®

Lee's Hi-Tech Ent. Co., Ltd.

<http://www.telecrane.com.tw>

www.telecrane.com.au

P.O.Box 455 South Hurstville NSW 2221 Australia

tel. 02 95708202

email. info@telecrane.com.au